

# Density<sup>®</sup> UNIK

Density<sup>®</sup> UNIK is the technological revolution of the fogging industry. Cold fog is the result of an international patent. Cold at all times, security fog is produced from the intensity of special high-amperage batteries, the Density<sup>®</sup> UNIK POWER PACK.

Developed and intended for domestic market, isolated mobile premises, vehicules and small shops of relative risks such as hairdressers, florists, etc...

The Density<sup>®</sup> UNIK fog generator is the solution to protect your goods and premises from relative risks by instantly repelling intruders.



Real sizes for comparison



## KEY POINTS



The smallest fog generator on the market.



Quick and easy installation.



Battery operation possible. Up to 6 months in the event of total loss of power supply.



Very low power consumption. Close to zero.



Do not heat-up! Fog is produced INSTANTLY. 2 international patents.



The Density UNIK recharge can shoot up to 8 times reducing drastically the costs.

## DENSITY<sup>®</sup> UNIK TYPICAL APPLICATIONS



## GENERAL SPECIFICATIONS

Weight	5 kg
Dimensions	300 mm x 200 mm x 150mm
Colors	White or Black
Power supply	9-24V - Battery operation possible
Heat-up time	System instantly ready
Autonomy on battery (POWER PACK)	Up to 6 months*

## FOG GENERATOR

Single shoot max time	60 seconds
Single shoot max fog output	100 m <sup>3</sup> (EN standard) - commercial 300 m <sup>3</sup>
Shooting time settings	3 options 15, 30 or 60 seconds
Maximum coverage with a UNIK Density cartridge	600 m <sup>3</sup> commercial
Number of full fog shots on a full fluid bag	From 2 to 8
External LED	3
Low fluid level indicator/error	Yes - red LED
Ready to shoot indicator	Yes - blue LED
Indicator of unit on	Yes - green LED
ABS lid	Yes
Inputs	3
PIR/ PANIC input	Yes
Outputs	3 (optional board relay)
Status and audio indicators on PCB	Yes
Shooting test and diagnostics (2 sec.)	Yes

## COMMUNICATION

Wired IP card and WiFi (ActiveCloud)	Yes** (optional)
WiFi antenna for ActiveCloud	Yes* (optional)
Access to ActiveCloud with remote monitoring/activation	Yes (free)

\* Autonomy is guaranteed for at least one 60 secs full shoot (unit without connected accessories)

\*\* Requires 12V power (via power supply or stepdown cable)

### Accessories for **Density® UNIK**

Active Cloud LAN/WiFi board (opt.) with cables

WiFi antenna module for Active Cloud

Orientable wall bracket

Single battery (12V 9Ah )

External fast charger

Internal 220v power supply

24-12 V adapter cable

Demo kit (receiver + keyfob)

### **Density®** refills

Fluid bag 125 ml **Density® UNIK**