

# Density<sup>®</sup>900 Lite

The easy installation fog generator, dedicated to the protection of premises up to 100m<sup>2</sup>. The Density<sup>®</sup> 900 Lite fog generator is the key to secure your valuables and permises by instantly repelling intruders.





#### FEATURES



To protect premises from 5 to 100 m².



Fast and dense, this fog generator produce 300 m<sup>3</sup> in 40 seconds.



### COMPATIBILITY



ActiveCloud board for secure connection (2x128bits encryption) wired or WiFi.



API available for software and hardware customisation.



Multidirectional nozzle adaptative to fit all installations types.

densityglobal.eu

#### **GENERAL SPECIFICATIONS**

Weight	8 kg	
Dimensions	390 mm x 300 mm x 130mm	
Colors	White or black	
Operating time without mains power	Over 1 hour	
Heating time	Around 2 hours	
Average power consumption after heat-up	37W	
Vertical mounting	Yes	
Horizontal mounting	Yes	
Usb port for computer monitoring (Windows and Linux)	Yes	
Adjustable nozzle	Yes	
Nozzle extention	Yes (optional)	

#### FOG GENERATOR

Single shoot max time	40 seconds	
Single shoot max fog output	300 m <sup>3</sup> (EN standard) - commercial 900 m <sup>3</sup>	
Shot characteristics	Programmable in seconds	
Fluid container system	1 L	
Number of full Fog releases on a full fluid bag	5	
2 cabled inputs:	Arming and shooting	
3 cabled outputs:	Empty bag, Shoot confirm and system failure	
Top internal riser for optional boards	Yes (optional)	
Side internal riser for optional boards	Yes (optional)	
RS232 Serial ports for dedicated option boards	Yes, 2	

## - ELECTRICAL SPECIFICATIONS

230 V AC or 120 V AC	
37 W	
170 W	
Not included	

#### Accessories for **Density® 900** Lite

Active Cloud LAN/WiFi board	Orientable wall bracket	Fluid bag 1000 ml <b>Density® 900</b> Lite
WiFi antenna module for Active Cloud	Desk stand wall bracket	Huid bag 1000 mi Density 700 Lite
Extra standard nozzle	Reverse shoot machines	
Extra inclined nozzle	Black painted cabinest (to add)	
Extra nozzle three holes	Black cover	
Nozzle extention 5 cm	White cover	
Nozzle extention 10 cm	Demo kit	
Serial 4 relay board		
(4 separate output signals)		

**Density**<sup>®</sup> refills